

Energy Efficiency Features	NewStyle Performance	Additional Information
Temperature Resistance:		
Winter Comfort: R-Value	5.91	A product's R-value is a measurement of its ability to keep heat in and cold out. The higher the R-value, the better that product is at retaining indoor warmth. ¹
Solar Heat Gain Coefficient	.17	A product's solar heat gain coefficient is a measurement of its ability to reduce heat from the sun. SHGC is expressed as a number between zero (none) and one (all). The lower a window coverings solar heat gain coefficient, the more heat it blocks. ²
Ultraviolet Protection	99%	A product's ability to block harmful ultraviolet rays is measured in terms of a percentage. The higher the rating, the greater the UV protection.
Sound Resistance/Sound Control:		
Sound Absorption	.10	Sound absorption ratings measure the amount of reflected sound absorbed. The scale for sound absorption is in a range from 0.00 to 1.00 where 1.00 means total, 100% absorption of sound. For example, 0.10 would indicate approximately 10% sound absorption.
Ventilation	Excellent	NewStyle Hybrid Shutters rate excellent in ventilation. When the louvers are fully open, air can flow freely through them.
Reduction in Energy Consumption	Excellent	NewStyle Hybrid Shutters are an excellent choice in window coverings to reduce home heating and cooling loss. The R-value performance of a double glazed low E glass window is increased by 42.5% when NewStyle Hybrid Shutters are used to cover the window. This correlates to an annual energy savings of 73.8%. ³

Indoor Air Quality Features:	NewStyle Performance	Additional Information
Lead	Passed	NewStyle Hybrid Shutters have been tested for lead and are below both the Environmental Protection Agency (EPA) and the American National Standards Institute (ANSI) standards for lead. ⁴
Formaldehyde	Passed	NewStyle Hybrid Shutters have been tested for formaldehyde and are below the Environmental Protection Agency (EPA) standards for formaldehyde. ⁵
Volatile Organic Compounds (VOCs)	Passed	NewStyle Hybrid Shutters have been tested for Volatile Organic Compounds (VOCs) and have been Greenguard Indoor Air Quality Certified by the Greenguard Environmental Institute. (GEI). ⁶
Resource Efficiency:	NewStyle Performance	Additional Information
Recyclable/Renewable Content – Product	Excellent	NewStyle Hybrid Shutters are made of an Ultra Light Density Fiberboard (ULDF). ULDF is made from recycled content.
Recyclable/Renewable Content - Packaging	Excellent	NewStyle Hybrid Shutters are packaged using 100% recyclable material of which 20% are from recycled goods. Hunter Douglas is continually implementing programs for recycling and reusing packaging materials.
Product Lifecycle	Excellent	NewStyle Hybrid Shutters have excellent performance and are built to last. They are also backed by the Hunter Douglas Lifetime Guarantee.

Site Maintenance Features:	NewStyle Performance	Additional Information
Safety	Excellent	With no cords or strings, NewStyle Hybrid Shutters are an ideal choice for families concerned with child and pet safety.
Ease of Operation	Excellent	NewStyle Hybrid Shutters are very easy to operate. Simply open or close them with the touch of a finger.
Care and Cleaning	Excellent	NewStyle Hybrid Shutters are easy to clean with a soft, dry cloth. Light dusting will keep them looking beautiful for years to come.

Sources:

¹ Results based on Low-E double glazed window with product.

² Results based on standard double glazed window with product.

³ Visit <http://extension.missouri.edu/explore/hesguide/intdes/gh2815.htm> for more information on energy savings of shutters.

⁴ The maximum allowable lead content in a product by the EPA standards is 600ppm or .06%. Visit www.epa.gov/lead for more information. The American National Standard for Safety of Corded Window Covering Products A100.1-2007 states that exterior components of the window covering which can be touched or ingested by young children shall be produced with no more than .02% lead by weight (or 200ppm). Visit www.ansi.org for more information.

⁵ The maximum allowable formaldehyde content in a product by the OSHA standards is 0.5ppm. Visit www.epa.gov/iaq/formalde.html for more information.

⁶ Visit www.greenguard.org for more information on Greenguard certification.